

DOCKET NO. NOKIA-00011



COPY OF PAPERS
ORIGINALLY FILED

PATENT

62888
P. Honksalo
07/24/02

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of : HARRI HONKSASALO ET AL.
U.S. Serial No. : 10/035,689
Filed : November 8, 2001
For : MAPPING OF INTERNET PROTOCOL BASED DATA
Group No. : 2681
Examiner : (Not Yet Assigned)

Commissioner for Patents
Washington, D. C. 20231

RECEIVED
JUL 15 2002
Technology Center 2600

Sir:

CERTIFICATE OF MAILING BY FIRST CLASS MAIL

The undersigned hereby certify that the enclosed:

- 1) Certified copy of United Kingdom Application No. 0027535.4; and,
- 2) Postcard Receipt.

relating to the above application, were sent to the Commissioner for Patents via First Class Mail in an envelope addressed to Commissioner for Patents, Washington, D.C. 20231 on July 3, 2002.

Date: July 3, 2002

Date: 3 July 02

Robert H. Kelly
Mailer

Robert H. Kelly
Robert H. Kelly
Registration No., 33,922

P.O. Box 802432
Dallas, Texas 75380
Phone: (214) 922-9221
Fax: (214) 969-7557
E-mail: rkelly@davismunck.com

This Page Blank (uspto)



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

RECEIVED

JUL 15 2002


Technology Center 2600

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.




P. Mahoney

Signed

Dated 13 November 2001.

**CERTIFIED COPY OF
PRIORITY DOCUMENT**



The Patent Office
Cardiff Road
Newport
Gwent NP9 1RH

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference	200524/JPR/JBS/ms	13NOV00 E582952-6 D00068 P01/7700 0.00-0027535.4
2. Patent application number (The Patent Office will fill in this part)	10 NOV 2000	0027535.4
3. Full name, address and postcode of the or of each applicant (underline all surnames)	NOKIA MOBILE PHONES LIMITED KEILALAHDENTIE 4 02150 ESPOO FINLAND	
Patents ADP number (if you know it)	5911995004	
If the applicant is a corporate body, give the country/state of its incorporation	FINLAND	
4. Title of the invention	MAPPING OF INTERNET PROTOCOL BASED DATA	
5. Name of your agent (if you have one)	PAGE WHITE & FARRER	
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	54 DOUGHTY STREET LONDON WC1N 2LS UNITED KINGDOM	
Patents ADP number (if you know it)	1255003	
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority application number (if you know it)
		Date of filing (day / month / year)
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day / month / year)
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body See note (d))	YES	

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form -

Description 12

Claim(s) 4

Abstract -

Drawing(s) 1

10. If you are also filing any of the following, state how many against each item.

Priority documents -

Translations of priority documents -

Statement of inventorship and right to grant of a patent (Patents Form 7/77) -

Request for preliminary examination and search (Patents Form 9/77) -

Request for substantive examination (Patents Form 10/77) -

Any other documents
(please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

JEFF WHITE & FARRER

10.11.2000

12. Name and daytime telephone number of person to contact in the United Kingdom

JEFF SWEETMAN - 020 7831 7929

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

MAPPING OF INTERNET PROTOCOL BASED DATA

FIELD OF INVENTION

The present invention relates to the field of radio telecommunications, and more particularly to mapping of data from an Internet Protocol (IP) environment into a format suitable for radio transmission.

The invention has been developed primarily for facilitating provision of IP-based services in a WCDMA-based mobile telephonic environment, and will be described hereinafter with reference to that application. However, it will be appreciated that the invention is not limited to use in that field.

20

BACKGROUND TO INVENTION

Over the last few years, a desire for improved data rate and more efficient use of dedicated frequency spectra has led to the proposal and adoption of wideband CDMA as a major standard for next generation mobile telephony. The most popular scheme is that being developed by the 3GPP group, which will be well known to those in the field of mobile telecommunications.

There has been a move over a similar period of time towards delivering data in packet form. One protocol for packet-based transmission is the Internet Protocol (IP) standard. Whilst IP-based transmission of data embodies certain efficiencies, it does have some disadvantages when applied to a mobile telecommunications environment.

35

5 For example, the ratio of header information to payload data
can often be relatively high. In an internet computing
context, such a limitation is of little consequence. However,
in a radio communications environment with limited spectrum
available, it is desirable to reduce this ratio. One proposal
10 presently being considered is the use of header compression,
which would reduce the total number of bits to be transmitted.

Proposed header compression schemes typically still require
transmission of an initial or periodic uncompressed header to
15 provide context for the subsequent compressed versions. These
uncompressed headers can be relatively large, and, when
combined with the payload data and signalling data required
for radio transmission, can require the use of relatively low
spreading factors. This has the undesirable impact of either
20 reducing available code-space (in a WCDMA system) or requiring
high puncture rates.

The most widely adopted specification for the third generation
of mobile telecommunications has been proposed, and is further
25 being developed, by the 3rd Generation Partnership Project
(3GPP). Code Division Multiple Access (CDMA) has emerged as
the most favoured technology for third generation
telecommunications, the wideband CDMA (WCDMA) embodiment
adopted by 3GPP being known as UTRA (Universal Terrestrial
30 Radio Access). WCDMA, and its application to third generation
mobile telephony and the 3GPP standards being developed, is
described in some detail in 3GPP Technical Specification
25.212, the contents of which are incorporated herein by cross
reference.

5 In UTRA, transport channels are used to deliver data from higher layers to the physical layers that deal with the mechanics of encoding and transmission over the air. Each transport channel carries data from a different source. This can include, for example, voice data, signalling data used by
10 the system during transmission or IP-based data such as multimedia communications or IP-voice data (along with the header data required for IP communication).

Once the physical layer receives the signal data, it is, amongst other things, spread using a spreading code. This is achieved by multiplying the data with a spreading code, which is pseudo-random in nature and of a particular length, the length of the code being referred to as the spreading factor. For a given bandwidth, a spreading factor 8 would result in
20 data at 1/8 the given chip rate.

Given a restricted bandwidth within which to operate, once packets of data reach a certain size, it becomes necessary to reduce the spreading factor to ensure that bandwidth of the
25 resultant signal falls within the available spectrum.

In the case of IP communications, and IP voice in particular, headers are used for signalling, routing and other ancillary data. The header for each packet can itself require
30 considerably more bits than the payload data within the packet, sometimes by a factor of 2 or more. The present UTRA standard proposed by 3GPP also requires that the header and payload data for a given channel be delivered on the same transport channel and therefore mapped to the same physical
35 channel (or coded composite transport channel).

5 Spreading of data for an IP voice connection results in some undesirable characteristics. Due to the size of the header, payload and signalling data, it may become necessary to use a relatively low spreading factor to ensure that the encoded signal remains within allocated spectrum. One difficulty with
10 this is that use of a low spreading factor code results in a removal of a relatively large number of orthogonal codes of higher spreading factor from the available code space.

SUMMARY OF INVENTION

15

According to a first aspect of the invention, there is provided a method of mapping internet protocol (IP) based data and signalling data for forming a single connection between a first station and a second station in a code division
20 multiple access (CDMA) system, using two or more sets of physical channels, each of the physical channels in each set utilising the same spreading factor as other physical channels in that set, the IP-based data including header data and application data, each of the header data, signalling data and
25 application data being assigned to at least one transport channel ("TrCH"), the method including the steps of:

- (a) mapping at least a first one of the transport channels to a first one of the sets of physical channels; and
- (b) mapping at least a second one of the transport channels
30 to a second one of the sets of physical channels.

Preferably, a first spreading factor is applied to the first set of physical channels on the basis of a data rate of the first one of the transport channels, and a second spreading
35 factor is applied to the second set of physical channels on

5 the basis of a data rate of the second one of the transport channels.

More preferably, the first spreading factor and the second spreading factor are different from each other.

10

In one form, the first spreading factor is constant, and the second spreading factor is changed over time. Preferably, wherein the second spreading factor is varied between first and second spreading factor values.

15

In a preferred embodiment, the size of the header is variable over time. Preferably in this embodiment, the size of the header varies over time depending upon the amount or type of header compression applied.

20

In one embodiment, a full header is initially transmitted and a compressed header is subsequently transmitted, the second spreading factor applied to the second set of physical channels being a relatively low value for the initial
25 transmission and being a relatively high value for the subsequent transmission.

Preferably, each of the sets of physical channels is defined by a coded composite transport channel (CCTrCH) in an UTRA-
30 based communications system.

In one form, one or more of the sets of physical channels includes a single physical channel. Alternatively or in addition, it is preferred that the one or more of the sets of
35 physical channels includes a plurality of physical channels.

5 In a second aspect, the present invention provides a network element for mapping internet protocol (IP) based data and signalling data to form a single connection between a first station and a second station in a code division multiple access (CDMA) system, using two or more sets of physical
10 channels, each of the physical channels in each set utilising the same spreading factor as other physical channels in that set, the IP-based data including header data and application data, each of the header data, signalling data and application data being assigned to at least one transport channel
15 ("TrCH"), the network element including mapping means configured for:

- (a) mapping at least a first one of the transport channels to a first one of the sets of physical channels; and
- (b) mapping at least a second one of the transport channels
20 to a second one of the sets of physical channels.

Preferably, a first spreading factor is applied to the first set of physical channels on the basis of a data rate of the first one of the transport channels, and a second spreading
25 factor is applied to the second set of physical channels on the basis of a data rate of the second one of the transport channels.

More preferably, the first spreading factor and the second
30 spreading factor are different from each other.

In one form, the first spreading factor is constant, and the second spreading factor is changed over time. Preferably, wherein the second spreading factor is varied between first
35 and second spreading factor values.

- 5 In a preferred embodiment, the size of the header is variable over time. Preferably in this embodiment, the size of the header varies over time depending upon the amount or type of header compression applied.
- 10 In one embodiment, a full header is initially transmitted and a compressed header is subsequently transmitted, the second spreading factor applied to the second set of physical channels being a relatively low value for the initial transmission and being a relatively high value for the
- 15 subsequent transmission.

Preferably, each of the sets of physical channels is defined by a coded composite transport channel (CCTrCH) in an UTRA-based communications system.

20

In one form, one or more of the sets of physical channels includes a single physical channel. Alternatively or in addition, it is preferred that the one or more of the sets of physical channels includes a plurality of physical channels.

25

BRIEF DESCRIPTION OF DRAWING

- Preferred embodiments of the invention will now be described, by way of example only, with reference to the accompanying
- 30 drawing. The drawing is a schematic of a transport channel multiplexing structure, embodied in a network element for implementing mapping of internet protocol (IP) based data and signalling data for a forming a single connection between a first station and a second station in a code division multiple
- 35 access (CDMA) system, according to the invention.

5 DETAILED DESCRIPTION OF PREFERRED AND OTHER EMBODIMENTS

In the preferred form, the invention is applied to a modified version of UTRA, a WCDMA standard defined by 3GPP. Two sets of physical channels, each defined by a CCTrCH, are used to provide a single connection. One or more TrCHs are mapped to each of the two CCTrCHs in such a way that the amount of code space removed from availability by the need for low spreading factors is minimised or at least reduced. The number of actual physical channels to which each CCTrCH is mapped is not critical.

The particular way in which the TrCHs are mapped to the CCTrCHs will vary depending upon, for example, the bandwidth available, the sizes of the headers, application/payload and signalling data in question, or whether compression has been employed.

EXAMPLE 1: IP-VOICE DATA, WITH OR WITHOUT HEADER COMPRESSION

25 TABLE 1

AMR 12.2 TTI=20ms	Header TrCH 1	Voice TrCH 2	Signalling TrCH 3
	Full header; or Compressed header (first or second order)	AMR IF2	3.4 kbps

Table 1 shows the contents of first, second and third transport channels (TrCH 1, 2 & 3 respectively) for one IP packet, mapping onto first and second CCTrCHs, at 1 voice

5 frame per RTP packet. The mapping of the transport channels to the physical channels via the CCTrCHs is as follows:

[TrCH 1 + TrCH2] is mapped to CCTrCH 1
[TrCH 3] is mapped to CCTrCH 2.

10

In this case, the voice data and its associated header data are mapped to the first CCTrCH channel. When the full header frame is delivered, the voice frame has to be omitted. Because of the size of the data packets involved (ie, the relatively high data rate required), a spreading factor (SF) of 128 may be employed. The signalling data for the connection is mapped to the second CCTrCH, but because of its lower data rate, a higher SF of 256 can be used. This results in substantial code space savings compared to mapping all of the data onto one CCTrCH, and even more so given that more efficient use of the code space is made possible. It will be appreciated that a very low spreading factor would be required if all of the data was to be mapped to a single CCTrCH. Alternatively, an unacceptably high puncture rate would need to be tolerated, as will be understood by those skilled in the art.

25
EXAMPLE 2: IP-VOICE DATA, WITH HEADER COMPRESSION

5 TABLE 2

AMR 12.2 TTI=20ms	Full Header TrCH 1	Compressed Header TrCH 2	Voice TrCH 3	Signalli ng TrCH 4
	Full header	Compressed header (first or second order)	AMR IF2	3.4 kbps

Table 2 shows the contents of first, second, third and fourth transport channels (TrCH 1, 2, 3 & 4 respectively) for IP voice frame mapping onto first and second CCTrCHs, at 1 voice frame per RTP packet. The mapping of the transport channels to physical channels via CCTrCHs is as follows:

- [TrCH 1] is mapped to CCTrCH 1
- [TrCH 2] is mapped to CCTrCH 2.
- [TrCH 3 + TrCH 4] is mapped to CCTrCH 1

In this case, the voice data and its associated header data are split from each other and delivered via different TrCHs to the physical layer. They are also mapped respectively to different CCTrCHs. It will be appreciated by those skilled in the art that the present 3GPP-99 standard does not allow delivery of associated header and voice data via different TrCHs, and so a slight to the standard needs to be made to account for this.

In this embodiment, the full header is only delivered at the start of the connection, to provide context for the subsequent compressed header data. The larger size of the uncompressed header data means that for it to be encoded along with the voice and signalling data on CCTrCH 1, an SF of 128 must be

5 used. However, once the full header has been transmitted, subsequent header data is supplied via the second physical channel, CCTrCH 2 at a spreading factor of 256. The voice and signalling data continue to be mapped to CCTrCH 1 at an SF of 128. This, again, results in more efficient use of available
10 code space.

It will be appreciated by those skilled in the art that many other mappings of a plurality of TrCHs to two (or more) CCTrCHs are available. The efficiencies of each will vary
15 depending upon such factors as the sizes of the headers, the types of compression used, and the available spectrum. Also, the specific SFs mentioned in relation to the preferred embodiments are exemplary only, and may differ depending upon factors such as the type of data being sent, the compression
20 used, and the available bandwidth.

In another aspect, the preferred form of the invention is applied at a network element, which will usually take the form of a base station. It will be appreciated, however, that
25 "network element" is intended to include any combination of sub-elements that are configured to implement the invention as defined in the relevant claims.

Figure 1 shows a multiplexing structure applied in the network
30 element. The steps involved are self-explanatory in view of the description of the embodiment above.

It will also be understood that the invention can be applied to other CDMA standards in which it is desired to map IP-based
35 data (such as IP-voice) onto physical channels. For this reason, it is to be understood that any references to acronyms

5 or abbreviations used in any particular embodiment of CDMA or WCDMA are intended to include any near equivalent components or features in other CDMA/WCDMA systems.

10 Although the preferred embodiments map multiple transport channels onto two channels with different SFs, ie CCTrCHs, in some case it can also be desirable to map the transport channels to more than two CCTrCHs. In some specific cases, for example, more efficient use can be made of available code space by splitting data over three or more channels, each of
15 which can then utilise a higher spreading factor.

It will be understood that the 3GPP standard to which the preferred embodiment applies is presently being developed and modified on an ongoing basis. Accordingly, there may some
20 technical protocol parameters that need to be modified to allow the invention to be implemented in some specific embodiments if it is to be implemented under that protocol in future. However, it is a routine matter to implement the invention using a proprietary standard based substantially on
25 the 3GPP protocol with suitable modifications.

The invention also has application to other types of IP data, such as IP encoded multimedia, or other packetised data protocols, especially those employing relatively high header
30 to payload ratios.

Although the invention has been described with reference to a number of specific embodiments, it will be appreciated by those skilled in the art that the invention can be embodied in
35 many other forms.

5 CLAIMS:

1. A method of mapping internet protocol (IP) based data and signalling data for forming a single connection between a first station and a second station in a code division multiple
10 access (CDMA) system, using two or more sets of physical channels, each of the physical channels in each set utilising the same spreading factor as other physical channels in that set, the IP-based data including header data and application data, each of the header data, signalling data and application
15 data being assigned to at least one transport channel ("TrCH"), the method including the steps of:
 - (a) mapping at least a first one of the transport channels to a first one of the sets of physical channels; and
 - (b) mapping at least a second one of the transport channels
20 to a second one of the sets of physical channels.
2. A method according to claim 1, wherein a first spreading factor is applied to the first set of physical channels on the basis of a data rate of the first one of the transport
25 channels, and a second spreading factor is applied to the second set of physical channels on the basis of a data rate of the second one of the transport channels.
3. A method according to claim 2, wherein the first
30 spreading factor and the second spreading factor are different from each other.
4. A method according to claim 2 or 3, wherein the first spreading factor is constant, and the second spreading factor
35 is changed over time.

5 5. A method according to claim 4, wherein the second spreading factor is varied between first and second spreading factor values.

6. A method according to claim 4 or 5, wherein the size of
10 the header is variable over time.

7. A method according to claim 6, wherein the size of the header varies over time depending upon the amount or type of header compression applied.

15

8. A method according to claim 6 or 7, wherein a full header is initially transmitted and a compressed header is subsequently transmitted, the second spreading factor applied to the second set of physical channels being a relatively low
20 value for the initial transmission and being a relatively high value for the subsequent transmission.

9. A method according to any one of the preceding claims, wherein each of the sets of is defined by a coded composite
25 transport channel (CCTrCH) in an UTRA-based communications system.

10. A method according to any one of the preceding claims, wherein one or more of the sets of physical channels includes
30 a single physical channel.

11. A method according to any one of the preceding claims, wherein one or more of the sets of physical channels includes a plurality of physical channels.

35

5 12. A network element for mapping internet protocol (IP)
based data and signalling data to form a single connection
between a first station and a second station in a code
division multiple access (CDMA) system, using two or more sets
of physical channels, each of the physical channels in each
10 set utilising the same spreading factor as other physical
channels in that set, the IP-based data including header data
and application data, each of the header data, signalling data
and application data being assigned to at least one transport
channel ("TrCH"), the network element including mapping means
15 configured for:

- (a) mapping at least a first one of the transport channels to
a first one of the sets of physical channels; and
- (b) mapping at least a second one of the transport channels
to a second one of the sets of physical channels.

20

13. A network element according to claim 12, wherein a first
spreading factor is applied to the first set of physical
channels on the basis of a data rate of the first one of the
transport channels, and a second spreading factor is applied
25 to the second set of physical channels on the basis of a data
rate of the second one of the transport channels.

14. A network element according to claim 13, wherein the
first spreading factor and the second spreading factor are
30 different from each other.

15. A network element according to claim 13 or 14, wherein
the first spreading factor is constant, and the second
spreading factor is changed over time.

35

5 16. A network element according to claim 15, wherein the second spreading factor is varied between first and second spreading factor values.

10 17. A network element according to claim 15 or 16, wherein the size of the header is variable over time.

18. A network element according to claim 17, wherein the size of the header varies over time depending upon the amount or type of header compression applied.

15

19. A network element according to claim 17 or 18, wherein a full header is initially transmitted and a compressed header is subsequently transmitted, the second spreading factor applied to the second set of physical channels being a relatively low value for the initial transmission and being a relatively high value for the subsequent transmission.

20

20. A network element according to any one of the preceding claims, wherein each of the sets of is defined by a coded composite transport channel (CCTrCH) in an UTRA-based communications system.

25

21. A network element according to any one of the preceding claims, wherein one or more of the sets of physical channels includes a single physical channel.

30

22. A network element according to any one of the preceding claims, wherein one or more of the sets of physical channels includes a plurality of physical channels.

35




Figure 1: Transport channel multiplexing structure for downlink

The single output data stream from the TrCH multiplexing, including DTX indication bits in downlink, is denoted *Coded Composite Transport Channel (CCTrCH)*. A CCTrCH can be mapped to one or several physical channels.

This Page Blank (uspto)